

Utility Vehicle

Model 6042KXC-X2



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Multi-use Truck
GENERAL SPECIFICATIONS	
Passenger Capacity	2
Range (loaded)	49.71 miles
Max. Speed (m/h)	16.78
Minimum Turning Radius (ft)	13.12
Max. Climbing Ability (loaded)	20%
Max. Movement After Brake	13.12 feet
Outer Dimension of rear closed van (ft)	3.28 x 3.28 x 3.28 ft
Overall Dimensions (ft)	9.65 x 4.59 x 5.68 ft
Max. Loading Weight (lbs)	793.66 lbs
Net Weight (lbs)	1499.14 lbs



CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + fiberglass body	S
Roof	Aluminum frame + fiberglass	S
Windshield	Toughened glass	S
Seats: 1) Backrest and Cushion 2) Armrest	Sponge + artificial leather Soft expanded plastic	S S
Seat Belt (2-point)	2 pcs per cart	O
Seat Belt (3-point)	2 pcs per cart	O
Hand Holder for Front Passenger	1 pc hand holder fixed under the roof	S
Side Rear View Mirror	2 pcs per cart	S
Floor	Bamboo + artificial leather	S
Dashboard	Forward/reverse switch, headlight indicator, turn signal indicator, ignition key, battery state indicator, ammeter, emergency switch; turn signal switch, headlight switch, windscreen wiper switch, horn button; Storage for miscellaneous items, Radio and tape player (\$60)	S
If with CD player	Replacing original Radio & Tape player With wire Or wireless	O O O
If with speedometer	\	S
Speaker for Radio and Tape Player	2 pcs	S
Lighting System	2 headlights, 2 front turn signals, 2 rear turn signals and 2 rear brake lights	S
Horn and Reverse Alarm	\	S
Battery	T605X 8 PCS	S
Motor (hp)	5.5	S
Controller	Curtis brand 1268	S
Training Gear	Gear and rack	S
Brake System	Rear and front drum pneumatic brake system	S
Accelerator	Stepless speed change	S
Front End and Front Suspension	Independent suspension	S
Rear End	With primary speed reducer and speed-change gear box	S
Rear Suspension	Steel plate suspension	S
Driving Mode	Rear wheel driving	S
Tire	20.5x8.0-10	S
Wheel	6J-10 steel wheel, wheel cap Aluminum wheel 10*7	S O
Enclosure	\	O
ACCESSORIES		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S
If without charger	\	O
Solar	Install and panel	O