

# Utility Vehicle

## Model 6062KXC-X6



Cruise Car, Inc.  
P: 941.929.1630  
www.cruiseincar.com

Descriptions:	Multi-use Truck
<b>GENERAL SPECIFICATIONS</b>	
Passenger Capacity	6
Motor Power (hp)	4.02
Battery Voltage (V)	6
Battery Quantity (pcs)	8
Range (loaded) based on flat road at a speed of 20km/h (km)	49.71
Max. Speed (m/h)	16.78
Minimum Turning Radius (ft)	15.75
Max. Climbing Ability (loaded)	20%
Max. Movement After Brake	13.12 feet
Rear box dimension (ft)	4.10 x 4.17 x 3.48
Overall Dimensions (ft)	12.01 x 4.59 x 5.94
Max. Loading Weight (lbs)	881.85 lbs
Net Weight (lbs)	1763.70 lbs



<b>CONFIGURATIONS</b> ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + fiberglass body	S
Roof	Aluminum frame + fiberglass	S
Windshield	Toughened glass	S
Seats: 1) Backrest and Cushion 2) Armrest	Sponge + artificial leather Soft expanded plastic	S S
Seat Belt (2-point)	2 pcs per cart	O
Seat Belt (3-point)	2 pcs per cart	O
Hand Holder for Front Passenger	1 pc hand holder fixed under the roof	S
Hand holder for rear passenger	2pcs, fixed on front backrest	S
Storage net	1pc each on backrest	S
Side Rear View Mirror	2 pcs per cart	S
Floor	Bamboo + artificial leather	S
Dashboard	Forward/reverse switch, headlight indicator, turn signal indicator, ignition key, battery state indicator, ammeter, emergency switch; turn signal switch, headlight switch, windscreen wiper switch, horn button; Storage for miscellaneous items, Radio and tape player	S
If with CD player	Replacing original Radio & Tape player With wire Or wireless	O O O
If with speedometer	\	S
Speaker for Radio and Tape Player	2 pcs	S
Lighting System	2 headlights, 2 front turn signals, 2 rear turn signals and 2 rear brake lights	S
Horn and Reverse Alarm	\	S
Battery	Trojan battery T605X 8 PCS	S
Motor	Chinese motor, 4KW	S
Controller	Curtis brand 1268	S
Training Gear	Gear and rack	S
Brake System	Rear and front drum pneumatic brake system	S
Accelerator	Stepless speed change	S
Front End and Front Suspension	Independent suspension	S
Rear End	With primary speed reducer and speed-change gear box	S
Rear Suspension	Steel plate suspension	S
Driving Mode	Rear wheel driving	S

Tire	20.5x8.0-10	S
Wheel	6J-10 steel wheel Aluminum wheel 10*7	S O
Enclosure	\	O
<b>ACCESSORIES</b>		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S
If without charger	\	O
Solar	\	O