

Kudo

Model 6112K-X11



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Personal Carrier (Passenger Car)	
GENERAL SPECIFICATIONS	6021H	6021H
Battery	T105 X 8 pcs	
Motor (hp)	7.0	
Controller	Curtis 1205	Curtis 1244
Passenger Capacity	11	
Range (loaded)	37.28 miles	
Max. Speed (m/h)	24.85	
Minimum turning radius (ft)	18.04	
Overall Dimensions (LxWxH) (ft)	13.29 x 4.82 x 6.10	
Max. Climbing Ability (loaded)	20%	
Max. Loading Weight (lbs)	1609 lbs	
Tare weight	2645.55 lbs	
Qty/40'	2 units	



CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + Fiberglass	S
Roof	Fiberglass + ABS, with hand holder	S
Windscreen	Toughened glass	S
Seats: 1) Backrest and Cushion 2) Armrest	Sponge + artificial leather Stainless steel	S S
Seat belt	2-point seatbelt	S
Floor	Bamboo board+ Non-slipping plastic	S
Side rear view mirror	One piece each side	S
Inner rear view mirror	One piece each cart	O
Overshadowing curtain	\	O
Windscreen wiper	\	S
DC-DC Converter	48V-12V	S
Lights	Front: 2 Headlights, 2 front turn signals; Back: 2 rear turn signals, 2 brake lights	S
Dahboard	Voltmeter, ammeter, speedometer, turn signal indicator, headlight indicator, emergency switch; Headlight switch, turn signal switch, wiper switch, horn button; Radio receiver and tape player	S
CD Player	Replacing original Radio & Tape player	O
Wired mircophone	\	O
Horn and reverse alarm	\	S
Cup drinker holder	1 pc	S
Speaker	2 pcs fixed on roof	S
Steering system	Rack and pinion steering system	S
Brake system	Front and rear drum hydraulic brake system	S
Front end and Suspension system	Independent suspension, cylinder hydraulic vibration absorber	S
Rear end and suspension system	Integrated rear end, steel plate spring suspension, cylinder hydraulic vibration absorber	S
Transmission system	Clutch, 4F+1R gear box, transmission shaft	S
Seat belt	2 point seat belt (8 pcs)	O
Tire	145/80-R12	S
Wheel	4J*12 Steel wheel, wheel cap 4J*12 Aluminum wheel	S O
ACCESSORIES		
Charger	China origin, input 110V~230V, 50Hz/60Hz, output 48V, 25A, 5m DC cable, 2.5m AC cable	S